

ACRYLIC SEALANT 310ML



Art.No. 0892 122310

Odorless one component acrylic based sealant

Application: Sealing of low and medium movement joints between various construction materials (wood, concrete, brick etc., sealing joints between windows, walls, doors etc.,) filling cracks in walls and on ceilings. Can be painted over once cured. (preliminary test required)

Instructions: The joints must be clean and free from dust, grease and rust. No primer is required for non-porous surfaces. On porous surfaces such as concrete, stone, cement and plaster. A primer (mixture of one part acrylic sealant and 4-5 parts of water) should be applied. Min/max joint width must be 5mm/25mm. The recommended joint depth/width ratio is 1 to 2. Application temperature is between +5 °C and +40 °C. Immediately after the application, smooth the sealant at once with a joint smoother. Excess sealant can be removed with a wet cloth. Keep the sealed joint dry at least for two hours. Cured sealant can be removed mechanically not suitable for permanent water storage.

Technical Data	
Base chemical	Acrylic dispersion
pH Value	7-8
Specific gravity	1,60 ± 0,03 gr/cm ³ (ASTM D792)
Tack free time	50 ± 20min (23°C and 50% R.H) (ASTM C679)
Skin forming	10 min
Curing rate	1 to 2mm/day (23°C and 50% R.H)
Elongation at break	250% (ASTM D412)
Max. permanent motion	5%
Temperature resistance	-10°C to 80°C
Application temperature	+5°C to 40°C
Hardness (shore A)	50

Additional Products



Art.No. 0891 310-AE - Cartridge gun



Art.No. 0697 4 - Wire brush



Art.No. 1715 660318 - Knife



Art.No. 1899 103001 - Safety goggles



Art.No. 0891 182 - Joint smoother



Art.No. 0899 404320 - Dotted gloves