

## DIESEL ENGINE OIL 10W-40 – SEMI-SYNTHETIC



**Würth diesel engine oil 10W-40 is a semi synthetic, high quality motor oil, characterized by a lower content of sulfated ash, phosphorus and sulfur (Lower SAPS).**

### Features and benefits:

- Recommended for all modern gasoline and diesel passenger car engines that meet EURO 4, EURO 5 and EURO 6 emission standards.
- The product is compatible with a diesel particulate filter (DPF) as well as a catalytic converter.
- It can also be used for vehicles with a pump-discharge system (VW 505 01).
- The oil change period is in accordance with the engine manufacturer's recommendations.

### Performance levels / Approvals:

API SN/SM/CF; ACEA C3-10  
 MB- 229.31/229.51,  
 Renault RN0700/RN0710, BMW Longlife - 04  
 GM dexos 2, Porsche A40 5W-40 12.3  
 Ford WSS-M2C917-A, VW 502 00/505 00/505 01

### Note:

Storage: In the original, well-closed packaging, and in rooms protected from moisture, atmosphere and fire, at a temperature of 5 to 30°C.

Description	Art.No.	Content
Diesel 10W-40, Semi-synthetic	<b>0897104007</b>	4 Ltr
	<b>0897104208</b>	208 Ltr

Technical Data	
SAE gradation	10W - 40
Viscosity at 100°C, mm <sup>2</sup> /s	13-15,00
Viscosity index	145
Flash point	232
Pour point, °C	-35