

PETROL ENGINE OIL 5W-30 – FULLY-SYNTHETIC



Würth petrol engine oil 5W-30 is a premium synthetic multigrade “Low SAPS” motor oil of the new generation.

Features and benefits:

- Primarily intended for lubrication of modern passenger vehicle engines of the Audi and Volkswagen group (VW, Audi, Seat, Škoda).
- Recommended for all gasoline and diesel engines of passenger vehicles.
- Primarily for those that meet the requirements of the standards regarding exhaust gas emissions: EURO 4, EURO 5 and EURO 6.
- For diesel engines with particulate filter (DPF) or exhaust gas recirculation (EGR).
- VW diesel engines with direct injection, especially models with a pump-injector system.
- Gasoline engines with a three-way catalyst (TWC- Three Way Catalyst).

Performance levels / Approvals:

ACEA C3-08 (2008) , MB-Approval 229.51
 Volkswagen VW50400 (2004)
 Volkswagen VW50700 (2004)
 BMW Longlife-04, Porsche C30

Note:

Storage: In the original, well-closed packaging, and in rooms protected from moisture, atmosphere and fire, at a temperature of 5 to 30 °C.

Description	Art.No.	Content
Petrol 5W-30, Fully-synthetic	0897530404	4 Ltr
	0897530208	208 Ltr

Technical Data	
SAE gradation	5W-30
Viscosity at 100 °C, mm ² /s	10,1
Viscosity at 40 °C, mm ² /s	57,9
Viscosity index	163
Flash point	220
Pour point, °C	-39
TBN, mg KOH / g	7,6