

PETROL ENGINE OIL 5W-40 – FULLY-SYNTHETIC



Würth petrol engine oil 5W-40 is a synthetic motor oil, which is used for lubrication of all types of modern gasoline and diesel engines of passenger vehicles. This oil is particularly suitable for turbo-compressed multi-valve and direct injection diesel engines.

Features and benefits:

- Particularly suitable for turbocharged multi-valve and direct injection diesel engines.
- It is intended for vehicles that are not equipped with a DPF filter.
- Protects the engine from wear and oxidation, is extremely suitable for easy cold start of the engine.
- Provides an extended oil change interval, or as recommended by the engine manufacturer.

Performance levels / Approvals:

API SN / CF, ACEA A3 / B4

MB 229.3 / MB 229.5 VW 502 00 / VW 505 00, BMW LL-01 / Porsche A40, Renault RN0700 / RN0710, PSA B71 2296; FIAT 9.55535-N2-M2

Note:

Storage: In the original, well-closed packaging, and in rooms protected from moisture, atmosphere and fire, at a temperature of 5 to 30°C.

Description	Art.No.	Content
Petrol 5W-40, Fully-synthetic	0897540004	4 Ltr
	0897540208	208 Ltr

Technical Data	
SAE gradation	5W - 40
Viscosity at 100 °C, mm ² /s	13,5-15,00
Viscosity index	155
Flash point	229
Pour point, °C	-39