

RADIATOR COOLANT G12



Art.No. 5862012401

Green

Art.No. 5862012402

Pink

Contents: 5L

P.Qty: 1

Radiator coolant G12 READY MIX -18 is an ethylene glycol based fluid that provides maintenance-free protection against freezing and boiling but also against corrosion. Is obtained through the use of virtually non-depleting corrosion inhibitors. It may be used with confidence in engines manufactured from cast iron, aluminium or combinations of the two metals, and in cooling systems made of aluminium or copper alloys.

Würth radiator coolant G12 ready mix -18 is particularly recommended for hi-tech engines where high temperature aluminium protection is important. It belongs to the group of oat (organic acid technology) antifreeze.

Change interval: 5 years.

It is ready mix product.

Features and benefits

- Excellent corrosion protection
- Cavitation protection
- Improved heat transfer
- Environmentally friendly

Performance levels

SRPS H.2.2.010 tip III, organski, BS 6580, ASTM D3306/4985, AFNOR NF R 15-601, VW/Audi/Seat/Skoda TL-774D/F (G12/G12+), MB 325.3, MAN 324-SNF, Ford WSS-M97B44-D/E, Opel General Motors GM 6277M/B040 1065, MTU MTL 5048, Volvo Penta/Trucks 128 6083/002 (produced after 2005), Deutz 0199-99-1115/6, Waukesha, Wärtsilä

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight. Recommended storage temperature: max. 40°C

Properties	Units	Typical values	Methods
Density at 20°C	g/cm ³	1,05	ASTM D1122
Color	-	Red / Green	Visualy
pH value	-	7.5 - 9	ASTM D1287
Reserve alkalinity	ml	Min 3	ASTM D1121
Boiling point	°C	105	ASTM D1120
Freezing point, max.	°C	-18	ASTM D1177